

MULTI-CROP SHREDDER

SPECIFICATIONS

MODELS	180	2408
Cutting Width	15' (4.6m)	20' (6 m)
Cutting Height	0-12" (0-30.5 cm)	0-12" (0-30.5 cm)
Knives	60	80
Minimum Tractor HP*	80 HP	100 HP
PTO Speed	1000 RPM	1000 RPM
Rotor Diameter	8 5/8" (21.9 cm)	8 5/8" (21.9 cm)
Wheels	[4] 15"x8" (38.1 cm x 20.3 cm)	[4] 15"x8" (38.1 cm x 20.3 cm)
Tires	[4] 9.5L tubeless	[4] 9.5L tubeless
Weight (approx.)	3,475 lbs (1,576 kg)	5,400 lbs (2,450 kg)
End Tow	N/A	Optional
Constant Velocity U-Joint on Tractor End	Standard	Standard
Overrunning Clutch	Standard	Standard
Hard Surface Knives	Optional	Optional

Hydraulic Cylinders not included.

*Horsepower requirements may vary with crop condition, type of crop and ground condition.
Specifications subject to change without notice.

M-C's 2 Year Extended Warranty and 5 Year Rotor Balance Warranty

In addition to our standard one year flail warranty, all new M-C Shredders carry a full second year warranty to the original buyer on all parts that flail under normal use. See warranty statement for complete details. Also, for a period of five years from the date of purchase, Mathews Company will re-balance M-C Shredder rotors free of charge to the original purchaser at our plant in Crystal Lake, provided the rotor went out of balance during normal use. This warranty does not cover damaged rotors. Labor and shipping charges to and from the factory are the owner's responsibility.



Mathews Company
www.mathewscompany.com

Crystal Lake, IL
phone: 1-815-459-2210
fax: 1-815-459-5889
email: international@mathewscompany.com

**GRAIN DRYER
SPECIALISTS**